

## Terrazzo Fertigung für Kapazität von 1000 m<sup>2</sup> / Schicht. Modell OCEM 1440

### Allgemeinedaten:

- **Typ:** komplette Fertigungslinie
- **Hersteller:**
- **Model:** OCEM 1440
- **Herstellungsjahr:**

### Bilder:



### Bedingungen:

Installation for the production of with capacity for 1.000m<sup>2</sup>/turn. Model OCEM 1440 terrazzo tiles. This installation includes the following equipment:

- 1 Concrete plant composed by  
FAIR FACE
  - 3 hoppers 2.500x2.500 with vibrating chutes in joint chassis
  - 1 weight feeder with 4 load cells
  - 2 conveyor belts to elevate material to the mixer
  - 1 rotary mixer for 250 L.
  - 1 chute from the mixer to the doser
  - 1 worm conveyor for cement
- BACK FACE
  - 2 hoppers 2.500x2.500 with vibrating chutes in joint chassis
  - 1 weight feeder with 4 load cells
  - 2 conveyor belts to elevate material to the rotary mixer of 250 l.
  - 1 chute from the mixer to the back doser
  - Full electric panel
- 1 OCEM press model OPA-1440, in operation when unmounted, consisting on
  - 1 back face carriage
  - 1 bucket conveyor and extractor belt for the back side surplus material



: IN0230415

- 1 hidraulic central
  - 1 pneumatic unit
  - 1 set of moulds for 1/400x400 mm
  - 1 mix spreader
  - 1 electric switchboard with automation
  - 1 mix doser OPA-1440
  
  - 1 vertical single extractor, composed by
    - 1 full pallet stacker
    - Extractor carriage
    - 1 empty pallet stacker
    - 1 intermediate gear
    - 1 electric installation
    - 1 electric switchboard
    -
  
  - 1 complete set of 40cmx40cm moulds
  
  - A variety of pallets with rubber backs with different finishes, for different tile formats; 40cmx40cm, 30cmx30cm, 25cmx25cm...
  
  - +/- 500 trays for pavement stacking and drying
- <!--[if gte mso 9]><xml> </xml><![endif]-->