

AUTOMATIC SACK FILLING AND SEWING LINE

General Specifications:

- **Type:** AUTOMATIC SACK FILLING AND SEWING LINE
- **Manufacturer:** GROUP PACK . TECHNIPES
- **Model:** LC 21 . FISCHBEIN
- **Manufacturing date:** 2011

Images:



Specifications:

<!--[if gte mso 9]><xml> </xml><![endif]-->

<!--[if gte mso 9]><xml> Normal0falsefalsefalseESX-NONEAR-SA </xml><![endif]--><!--[if gte mso 9]><xml> </xml><![endif]--><!--[if gte mso 10]> <style> /* Style Definitions */ table.MsoNormalTable {mso-style-name:"Tabla normal"; mso-tstyle-rowband-size:0; mso-tstyle-colband-size:0; mso-style-noshow:yes; mso-style-priority:99; mso-style-parent:""; mso-padding-alt:0cm 5.4pt 0cm 5.4pt; mso-para-margin-top:0cm; mso-para-margin-right:0cm; mso-para-margin-bottom:10.0pt; mso-para-margin-left:0cm; line-height:115%; mso-pagination:widow-orphan; font-size:11.0pt; font-family:"Calibri", "sans-serif"; mso-ascii-font-family:Calibri; mso-ascii-theme-font:minor-latin; mso-hansi-font-family:Calibri; mso-hansi-theme-font:minor-latin; mso-ansi-language:ES; mso-fareast-language:EN-US;} </style> Complete automatic sack filling and sewing line for powdered products such as flour mixes.

TYPE OF PRODUCT: powdered flour and powdered products in general

WEIGHTS: de 5kgs a 25kgs

DENSIDAD: 0,6KG/LTR

TYPE OF SACKS: plastic, paper, raffia

DENSIDAD : 0.6 KG / LITRO

Capacity: 180/200 sacks per hour



: AL0790616

Includes:

- GROUP PACK sack filler developed by TECHNIPES, model LC-21 with two dosing endless screws of 1000mm, feeding hopper with 70x55mm.
- Control desk
- Conveyor belt with 2300x780x1100mm
- Sack sewing machine: FISCHBEIN model 2700, year: 1997. Length of the sewing 7,2mm; max. thickness of the material to sew 6,5mm; speed: 1900 rev.per minute
- Feeder for the sack sewing machine
 - OPTIONAL: stainless Steel endless screw for powder feeding with 3300mm length and 150mm of diameter with an inclination of 50° from 0 level . Stainless steel endless screw for powder feeding with 3500mm length and 150mm diameter with a supporting structure for feeding from 2500mm height
 - OPTIONAL: BYPASS symmetrical valve with 3 pneumatic drive ways. 1 inlet and 2 outlets. Built in stainless steel